

**MATERIALS:**TUBE: NeopreneCOVER: NeopreneREINFORCEMENT: NylonFEMALE UNIONS: Stainless SteelCONTROL UNITS: Steel Cable and Hardware**NSF 372- LEAD FREE**

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

QTY.	PART No.	SIZE (in.)	OAL (in.)	W/P (psi) 200°F	COMP. (in.)	ELONG. (in.)	LAT. (in.)	ANG. (°)	WT. (lbs.)
	SEMSDU-075	3/4	8	150	7/8	1/4	7/8	30	2
	SEMSDU-100	1	8	150	7/8	1/4	7/8	25	3
	SEMSDU-125	1-1/4	8	150	7/8	1/4	7/8	25	4
	SEMSDU-150	1-1/2	8	150	7/8	1/4	7/8	20	5
	SEMSDU-200	2	8	150	7/8	1/4	7/8	15	6
	SEMSDU-250	2-1/2	8 7/8	150	7/8	1/4	7/8	12	8
	SEMSDU-300	3	9	150	7/8	1/4	7/8	10	10

1. This flexible joint should be installed the length shown on drawing.
2. Piping and equipment connected by this flexible joint must be properly anchored and/or guided.
3. Not intended for torsion.

CUSTOMER \_\_\_\_\_  
 PROJECT \_\_\_\_\_  
 ENGINEER \_\_\_\_\_  
 ARCHITECT \_\_\_\_\_  
 PRO./PO No. \_\_\_\_\_



**SOUTHEASTERN HOSE, INC.**  
 Bremen, GA 30110

**DOUBLE SPHERE FEMALE UNION**  
 w/ CONTROL UNITS  
**SUBMITTAL DATA**

DESCRIPTION: